

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : GPP 1119 D TH H
Product code : PMA-GPP-1119-D-TH

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Colouring agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Heraeus Tokmak A.S.
Kemalpaşa O.S.B. Mah. 37. Sok. No: 6 35170 Ulucak Kemalpaşa
İzmir
TURKEY
T +90 (232) 877 2410
hakan.kiran@heraeus.com - www.heraeustokmak.com

1.4. Emergency telephone number

Emergency number : +90 (232) 877 2410

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1B	H350
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause cancer. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

GHS08

GHS09

Signal word (CLP) :

Danger

Contains :

1-naphtol, Peppermint oil, Naphthenic acids, vanadyl complexes , Butan-1-ol, Formaldehyde, Naphthenic acid

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H350 - May cause cancer. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P261 - Avoid breathing mist, dust. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P391 - Collect spillage. P501 - Dispose of contents and container to an approved waste disposal plant.
Extra phrases	: Restricted to professional users. For professional users only.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Urea, polymer with formaldehyde, butylated	CAS-No.: 68002-19-7 EC-No.: 614-202-7	≥ 5 – < 10	Aquatic Chronic 4, H413
P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	CAS-No.: 25085-50-1 EC-No.: 472-160-3	≥ 5 – < 10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Butan-1-ol	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6	≥ 3 – < 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
xylene substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	≥ 3 – < 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
Naphthenic acid	CAS-No.: 1338-24-5 EC-No.: 215-662-8	≥ 1 – < 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
1-naphthol	CAS-No.: 90-15-3 EC-No.: 201-969-4 EC Index-No.: 604-029-00-5	≥ 1 – < 3	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Silver(1+) neodecanoate	CAS-No.: 68683-18-1 EC-No.: 272-065-5	≥ 1 – < 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Naphthenic acids, vanadyl complexes	CAS-No.: 68553-60-6 EC-No.: 271-395-7	≥ 1 – < 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
sulfur	CAS-No.: 7704-34-9 EC-No.: 231-722-6 EC Index-No.: 016-094-00-1	≥ 1 – < 3	Skin Irrit. 2, H315
Spikoel	CAS-No.: 8016-78-2 EC-No.: 284-290-6	≥ 1 – < 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315
4-tert-butylphenol substance listed as REACH Candidate substance identified as having endocrine disrupting properties	CAS-No.: 98-54-4 EC-No.: 202-679-0 EC Index-No.: 604-090-00-8	≥ 0.1 – < 1	Repr. 2, H361f Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 1, H410
Peppermint oil	CAS-No.: 8006-90-4	≥ 0.1 – < 1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
ethylbenzene substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4	≥ 0.1 – < 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332
2-ethylhexanoic acid	CAS-No.: 149-57-5 EC-No.: 205-743-6 EC Index-No.: 607-230-00-6	≥ 0.1 – < 1	Repr. 2, H361d
Formaldehyde substance with a Community workplace exposure limit	CAS-No.: 50-00-0 EC-No.: 200-001-8 EC Index-No.: 605-001-00-5	0.1 – 0.2	Carc. 1B, H350 Muta. 2, H341 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Skin Sens. 1, H317
Bismuth tris(2-ethylhexanoate)	CAS-No.: 67874-71-9 EC-No.: 267-499-7	≥ 0.1 – < 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC-No.: 245-018-1	≥ 0.1 – < 1	Repr. 2, H361
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6	≥ 0.01 – < 0.1	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Formaldehyde	CAS-No.: 50-00-0 EC-No.: 200-001-8 EC Index-No.: 605-001-00-5	(0.2 ≤C ≤ 100) Skin Sens. 1, H317 (5 ≤C < 25) Eye Irrit. 2, H319 (5 ≤C < 25) Skin Irrit. 2, H315 (5 ≤C ≤ 100) STOT SE 3, H335 (25 ≤C ≤ 100) Skin Corr. 1B, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Kerosine (petroleum) (8008-20-6)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Kerosin (Erdöl) (C9 – C14 Aliphaten)
AGW (OEL TWA) [1]	Siehe TRGS 900, Nummer 2.9
Remark	AGS - Ausschuss für Gefahrstoffe; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 3
IOEL TWA [ppm]	20 ppm

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9)

IOEL STEL	290 mg/m ³
IOEL STEL [ppm]	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations

4-tert-butylphenol (98-54-4)

Germany - Occupational Exposure Limits (TRGS 900)

Local name	4-tert-Butylphenol
AGW (OEL TWA) [1]	0.5 mg/m ³
AGW (OEL TWA) [2]	0.08 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900

Germany - Biological limit values (TRGS 903)

Local name	4-tert-Butylphenol (p-tert-Butylphenol) (ptBP)
Biological limit value	2 mg/l Parameter: 4-tert-Butylphenol (p-tert-Butylphenol) (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 05/2013 DFG
Regulatory reference	TRGS 903

Formaldehyde (50-00-0)

EU - Binding Occupational Exposure Limit (BOEL)

Local name	Formaldehyde
BOEL TWA	0.37 mg/m ³ 0.62 mg/m ³ (Limit value for the health care, funeral and embalming sectors until 11 July 2024)
BOEL TWA [ppm]	0.3 ppm 0.5 ppm (Limit value for the health care, funeral and embalming sectors until 11 July 2024)
BOEL STEL	0.74 mg/m ³
BOEL STEL [ppm]	0.6 ppm
Notes	Dermal sensitisation
Regulatory reference	DIRECTIVE (EU) 2019/983 (amending Directive 2004/37/EC)

Germany - Occupational Exposure Limits (TRGS 900)

Local name	Formaldehyd
AGW (OEL TWA) [1]	0.37 mg/m ³
AGW (OEL TWA) [2]	0.3 ppm
Peak exposure limitation factor	2(I)

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Formaldehyd (50-00-0)	
Remark	AGS - Ausschuss für Gefahrstoffe; Sh - Hautsensibilisierender Stoff; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; X - Krebserzeugender Stoff der Kat. 1A oder 1B oder krebserzeugende Tätigkeit oder Verfahren nach § 2 Absatz 3 Nr. 4 der Gefahrstoffverordnung – es ist zusätzlich § 10 GefStoffV zu beachten
Regulatory reference	TRGS900
xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Xylol (alle Isomeren)
AGW (OEL TWA) [1]	220 mg/m ³
AGW (OEL TWA) [2]	50 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Xylol (alle Isomere)
Biological limit value	2000 mg/l Parameter: Methylhippur-(Tolur-) säure (alle Isomere) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylbenzene
IOEL TWA [ppm]	100 ppm
IOEL STEL	884 mg/m ³
IOEL STEL [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Ethylbenzol
AGW (OEL TWA) [1]	88 mg/m ³
AGW (OEL TWA) [2]	20 ppm

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich)
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Ethylbenzol
Biological limit value	250 mg/g creatinine Parameter: Mandelsäure plus Phenylglyoxylsäure - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
phthalic anhydride (85-44-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Phtalic anhydride
Remark	Respiratory sensitizer; skin sensitizer. (Year of adoption 2010)
Regulatory reference	SCOEL Recommendations
Butan-1-ol (71-36-3)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Butan-1-ol
AGW (OEL TWA) [1]	310 mg/m ³
AGW (OEL TWA) [2]	100 ppm
Peak exposure limitation factor	1(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Butan-1-ol (1-Butanol)
Biological limit value	2 mg/g creatinine Parameter: Butan-1-ol (1-Butanol) (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: d) vor nachfolgender Schicht - Festlegung/Begründung: 05/2013 DFG 10 mg/g creatinine Parameter: Butan-1-ol (1-Butanol) (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 05/2013 DFG
Regulatory reference	TRGS 903

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Dust/aerosol mask with filter type P1. Dustproof clothing.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Waxy.
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Solubility	: Practically insoluble in : Water. (20 °C). (1013 hPa).
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: 2000 mPa·s (70 °C)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

dimethyl terephthalate (120-61-6)	
LD50 oral	> 3200 mg/kg bodyweight Animal: other., Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:
Bismuth tris(2-ethylhexanoate) (67874-71-9)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
2-ethylhexanoic acid, zirconium salt (22464-99-9)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
Spikoel (8016-78-2)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Formaldehyde (50-00-0)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
1-naphthol (90-15-3)	
STOT-single exposure	May cause respiratory irritation.
cyclohexanol (108-93-0)	
STOT-single exposure	May cause respiratory irritation.
Camphor (76-22-2)	
STOT-single exposure	May cause damage to organs.
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9)	
STOT-single exposure	May cause drowsiness or dizziness.
Rhodium tris(2-ethylhexanoate) (20845-92-5)	
STOT-single exposure	May cause drowsiness or dizziness.
Silver(1+) neodecanoate (68683-18-1)	
STOT-single exposure	May cause respiratory irritation.
phthalic anhydride (85-44-9)	
STOT-single exposure	May cause respiratory irritation.
Butan-1-ol (71-36-3)	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Bismuth tris(2-ethylhexanoate) (67874-71-9)	
NOAEL (subchronic, oral, animal/male, 90 days)	180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:
NOAEL (subchronic, oral, animal/female, 90 days)	205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:
2-ethylhexanoic acid, zirconium salt (22464-99-9)	
NOAEL (subchronic, oral, animal/male, 90 days)	180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:
NOAEL (subchronic, oral, animal/female, 90 days)	205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
Naphthenic acid (1338-24-5)	
NOAEL (oral, rat, 90 days)	302 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
Aspiration hazard	: Not classified
GPP 1119 D TH H	
Viscosity, kinematic	Not applicable

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Not rapidly degradable	

dimethyl terephthalate (120-61-6)	
LC50 - Fish [1]	> 5.37 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 23.5 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	61.5 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	1.72 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Bismuth tris(2-ethylhexanoate) (67874-71-9)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
2-ethylhexanoic acid, zirconium salt (22464-99-9)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 0.17 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
Naphthenic acid (1338-24-5)	
LC50 - Fish [1]	≈ 5.62 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	≈ 20 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 29.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	≈ 17.7 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	≈ 29.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	≈ 18.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
4-tert-butylphenol (98-54-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 3077	UN 3077	UN 3077	UN 3077	UN 3077

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde)	Environmentally hazardous substance, solid, n.o.s. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde)
Transport document description				
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butan-1-ol ; Naphthenic acid ; 1-naphtol ; Naphthenic acids, vanadyl complexes ; Peppermint oil ; Formaldehyde), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport


Classification code (ADR)	: M7
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5kg
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P002, IBC08, LP02, R001
Special packing provisions (ADR)	: PP12, B3
Mixed packing provisions (ADR)	: MP10
Portable tank and bulk container instructions (ADR)	: T1, BK1, BK2, BK3
Portable tank and bulk container special provisions (ADR)	: TP33
Tank code (ADR)	: SGAV, LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V13
Special provisions for carriage - Bulk (ADR)	: VC1, VC2
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazard identification number (Kemler No.) : 90
Orange plates :



Tunnel restriction code (ADR) : -

Transport by sea

Special provisions (IMDG) : 274, 335, 966, 967, 969
Limited quantities (IMDG) : 5 kg
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP02, P002
Special packing provisions (IMDG) : PP12
IBC packing instructions (IMDG) : IBC08
IBC special provisions (IMDG) : B3
Tank instructions (IMDG) : BK1, BK2, BK3, T1
Tank special provisions (IMDG) : TP33
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A
Stowage and handling (IMDG) : SW23

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y956
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 956
PCA max net quantity (IATA) : 400kg
CAO packing instructions (IATA) : 956
CAO max net quantity (IATA) : 400kg
Special provisions (IATA) : A97, A158, A179, A197
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M7
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 kg
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T* B**
Equipment required (ADN) : PP, A
Number of blue cones/lights (ADN) : 0
Additional requirements/Remarks (ADN) : * Only in the molten state. ** For carriage in bulk see also 7.1.4.1. *** Only in the case of transport in bulk.

Rail transport

Classification code (RID) : M7
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5kg
Excepted quantities (RID) : E1
Packing instructions (RID) : P002, IBC08, LP02, R001
Special packing provisions (RID) : PP12, B3
Mixed packing provisions (RID) : MP10
Portable tank and bulk container instructions (RID) : T1, BK1, BK2, BK3
Portable tank and bulk container special provisions (RID) : TP33
Tank codes for RID tanks (RID) : SGAV, LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W13
Special provisions for carriage – Bulk (RID) : VC1, VC2
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE11

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazard identification number (RID) : 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
28.	Formaldehyde	Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.
72.	Formaldehyde	The substances listed in column 1 of the Table in Appendix 12

Contains a substance on the REACH candidate list in concentration $\geq 0.1\%$ or with a lower specific limit: 4-tert-butylphenol (EC 202-679-0, CAS 98-54-4)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Storage class (LGK, TRGS 510) : LGK 6.1D - Non-combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

GPP 1119 D TH H

Safety Data Sheet

according to Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.