

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
 Product name : Organometallic dye for industrial use  
 Product code : GGP 2046-10% H

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Industrial use  
 Use of the substance/mixture : Dyestuff/pigment

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Heraeus Tokmak A.S.  
 Kemalpaşa O.S.B. Mah. 37. Sok. No: 6  
 35170 Ulucak Kemalpaşa  
 İzmir - TURKEY  
 T +90 (232) 877 2410  
[hakan.kiran@heraeus.com](mailto:hakan.kiran@heraeus.com) - [www.heraeustokmak.com](http://www.heraeustokmak.com)

### 1.4. Emergency telephone number

Emergency number : +90 (232) 877 2410

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410
Full text of H statements : see section 16	

#### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS05

GHS07

GHS09

Signal word (CLP) :

Danger

Contains :

Oils, spike; Rosemary oil; Fennel oil, sweet; Oils, peppermint; Pine oil; Naphthenic acid; acetic acid 100%; rosin; colophony; Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours, spray, mist, gas. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. P321 - Specific treatment (see supplemental first aid instruction on this label). P391 - Collect spillage. P501 - Dispose of contents and container to a hazardous or special waste collection point.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oils, spike	CAS-No.: 8016-78-2 EC-No.: 616-988-7	≥ 10 – < 25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
cyclohexanol	CAS-No.: 108-93-0 EC-No.: 203-630-6 EC Index-No.: 603-009-00-3	≥ 10 – < 25	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	CAS-No.: 68410-23-1 EC-No.: 614-452-7	≥ 10 – < 25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411
Rosemary oil	CAS-No.: 8000-25-7 EC-No.: 616-767-5	≥ 5 – < 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
cyclohexanone	CAS-No.: 108-94-1 EC-No.: 203-631-1 EC Index-No.: 606-010-00-7	≥ 5 – < 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetic acid 100% (Note B)	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6	≥ 1 – < 3	Flam. Liq. 3, H226 Skin Corr. 1A, H314
Naphthenic acid	CAS-No.: 1338-24-5 EC-No.: 215-662-8	≥ 1 – < 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Abietic acid	CAS-No.: 514-10-3 EC-No.: 208-178-3	≥ 1 – < 3	Not classified
Pine oil	CAS-No.: 8002-09-3 EC-No.: 692-006-0	≥ 1 – < 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Naphthenic acids, vanadyl complexes	CAS-No.: 68553-60-6 EC-No.: 271-395-7	≥ 0.1 – < 1	Not classified
Oils, peppermint	CAS-No.: 8006-90-4 EC-No.: 616-900-7	≥ 0.1 – < 1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Bismuth tris(2-ethylhexanoate)	CAS-No.: 67874-71-9 EC-No.: 267-499-7	≥ 0.1 – < 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d
Chromium tris((2-ethylhexanoate)	CAS-No.: 3444-17-5 EC-No.: 222-357-3	≥ 0.1 – < 1	Aquatic Chronic 3, H412
rosin; colophony	CAS-No.: 8050-09-7 EC-No.: 232-475-7 EC Index-No.: 650-015-00-7	≥ 0.1 – < 1	Skin Sens. 1, H317
1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one	CAS-No.: 76-22-2 EC-No.: 200-945-0	≥ 0.1 – < 1	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302 Flam. Sol. 2, H228 STOT SE 2, H371
Kerosine (petroleum); Straight run kerosine; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).]	CAS-No.: 8008-20-6 EC-No.: 232-366-4 EC Index-No.: 649-404-00-4	≥ 0.1 – < 1	Asp. Tox. 1, H304
Larch, Larix decidua, ext.	CAS-No.: 90046-19-8 EC-No.: 289-987-9	≥ 0.1 – < 1	Not classified
Fennel oil, sweet	CAS-No.: 84455-29-8 EC-No.: 282-892-3	≥ 0.1 – < 1	Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351 Aquatic Chronic 2, H411
Naphtha (petroleum), full-range straight-run; Low boiling point naphtha; [A complex combination of hydrocarbons produced by distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately- 20°C to 220°C (- 4 °F to 428°F).] (Note P)	CAS-No.: 64741-42-0 EC-No.: 265-042-6 EC Index-No.: 649-265-00-X	≥ 0.01 – < 0.1	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lavandin Oil	CAS-No.: 8022-15-9 EC-No.: 617-009-6	≥ 0.01 – < 0.1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
2-ethylhexanoic acid	CAS-No.: 149-57-5 EC-No.: 205-743-6 EC Index-No.: 607-230-00-6	≥ 0.01 – < 0.1	Repr. 2, H361d
Eucalyptus oil	CAS-No.: 8000-48-4 EC-No.: 616-775-9	≥ 0.01 – < 0.1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Specific concentration limits		
Name	Product identifier	Specific concentration limits
acetic acid 100%	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6	( 10 ≤C < 25) Eye Irrit. 2, H319 ( 10 ≤C < 25) Skin Irrit. 2, H315 ( 25 ≤C < 90) Skin Corr. 1B, H314 ( 90 ≤C < 100) Skin Corr. 1A, H314

Note B : Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: "nitric acid ... %".

In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a ght/weight basis.

Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product. In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).  
Unsuitable extinguishing media : Strong water jet.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour. Keep away from ignition sources (including static discharges). Contact with combustible material may cause fire.  
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.  
Reactivity in case of fire : At high temperature may liberate dangerous gases.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

- Precautionary measures fire : Approach from upwind. Use water spray or fog for cooling exposed containers. Keep away from combustible materials.  
Firefighting instructions : Use water spray or fog for cooling exposed containers. Cool adjacent tanks / containers / drums with water jet. Do not allow water to enter the vessels, a violent reaction may occur. Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. Keep upwind. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.  
Other information : High temperature decomposition products are harmful by inhalation. Inhalation of vapour can cause breathing difficulties.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not touch or walk on the spilled product. Evacuate unnecessary personnel. Mark out the contaminated area with signs and prevent access to unauthorized personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Only qualified personnel equipped with suitable protective equipment may intervene.  
Emergency procedures : Avoid contact with skin and eyes. Do not touch spilled material. Evacuate unnecessary personnel. Keep public away from danger area. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Comply with the safety instructions.  
Methods for cleaning up : Notify authorities if product enters sewers or public waters. Clean up any spills as soon as possible, using an absorbent material to collect it. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Sweep or shovel spills into appropriate container for disposal. Minimise generation of dust.  
Other information : Dispose of materials or solid residues at an authorized site. Dispose of contaminated materials in accordance with current regulations.

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Use adequate ventilation to keep vapour concentrations below applicable standard. Take all necessary technical measures to avoid or minimize the release of the product on the workplace.
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid dust formation. Avoid prolonged and repeated contact with skin. Contaminated work clothing should not be allowed out of the workplace. Do not spray on an open flame or other ignition source.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment. Ensure adequate ventilation, especially in confined areas. Comply with applicable regulations.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible products	: Strong acids. Strong bases. Strong oxidizing agents. Peroxides.
Incompatible materials	: Extremely high or low temperatures.
Heat and ignition sources	: Do not smoke. KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
Information on mixed storage	: Keep away from food, drink and animal feeding stuffs.
Storage area	: Avoid: Extremely high or low temperatures. Heat and ignition sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National occupational exposure and biological limit values

1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one (76-22-2)	
<b>France - Occupational Exposure Limits</b>	
Local name	Camphre
VME (OEL TWA)	12 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	2 ppm
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Spain - Occupational Exposure Limits</b>	
Local name	Alcanfor sintético
VLA-ED (OEL TWA) [1]	13 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	2 ppm
VLA-EC (OEL STEL)	19 mg/m <sup>3</sup>

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one (76-22-2)</b>	
VLA-EC (OEL STEL) [ppm]	3 ppm
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>Kerosine (petroleum); Straight run kerosine; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).] (8008-20-6)</b>	
<b>Spain - Occupational Exposure Limits</b>	
Local name	Queroseno (combustible de aviación)
VLA-ED (OEL TWA) [1]	200 mg/m <sup>3</sup>
Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>rosin; colophony (8050-09-7)</b>	
<b>Spain - Occupational Exposure Limits</b>	
Local name	Resina núcleo de soldadura (Colofonia)
Notes	m (Los productos de descomposición térmica en el ambiente de la resina núcleo de soldadura, colo-fonia, tienen un marcado carácter sensibilizante, lo que aconseja reducir la exposición laboral a los mismos lo máximo posible), Sen (Sensibilizante).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>acetic acid 100% (64-19-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Acetic acid
IOEL TWA	25 mg/m <sup>3</sup>
IOEL TWA [ppm]	10 ppm
IOEL STEL	50 mg/m <sup>3</sup>
IOEL STEL [ppm]	20 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
<b>France - Occupational Exposure Limits</b>	
Local name	Acide acétique
VME (OEL TWA)	25 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	25 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	10 ppm
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: Arrête du 27 septembre 2019)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Essigsäure
AGW (OEL TWA) [1]	25 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	2(l)

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>acetic acid 100% (64-19-7)</b>	
Remark	DFG,EU,Y
Regulatory reference	TRGS900
<b>Spain - Occupational Exposure Limits</b>	
Local name	Ácido acético
VLA-ED (OEL TWA) [1]	25 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	10 ppm
VLA-EC (OEL STEL)	37 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	15 ppm
Notes	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>cyclohexanone (108-94-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Cyclohexanone
IOEL TWA	40.8 mg/m <sup>3</sup>
IOEL TWA [ppm]	10 ppm
IOEL STEL	81.6 mg/m <sup>3</sup>
IOEL STEL [ppm]	20 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>France - Occupational Exposure Limits</b>	
Local name	Cyclohexanone
VME (OEL TWA)	40.8 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	81.6 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	20 ppm
Note (FR)	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Cyclohexanon
AGW (OEL TWA) [1]	80 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	20 ppm
Peak exposure limitation factor	1(I)
Remark	AGS;EU;H;Y
Regulatory reference	TRGS900



# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexanone (108-94-1)	
<b>Italy - Occupational Exposure Limits</b>	
Local name	Cicloesanone
OEL TWA	40.8 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	81.6 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Notes	pelle
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Spain - Occupational Exposure Limits</b>	
Local name	Ciclohexanona
VLA-ED (OEL TWA) [1]	41 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	10 ppm
VLA-EC (OEL STEL)	82 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	20 ppm
Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), VLB® (Agente químico que tiene Valor Límite Biológico).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>Spain - Biological limit values</b>	
Local name	Ciclohexanona
BLV	80 mg/l Parámetro: 1,2-Ciclohexanodiol - Medio: Orina - Momento de muestreo: Final de la semana laboral - Notas: I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos), S (Significa que el indicador biológico es un indicador de exposición al agente químico en cuestión, pero la interpretación cuantitativa de su medida es ambigua (semicuantitativa). Estos indicadores biológicos deben utilizarse como una prueba de selección (screening) cuando no se pueda realizar una prueba cuantitativa o usarse como prueba de confirmación, si la prueba cuantitativa no es específica y el origen del determinante es dudoso), Con hidrólisis 8 mg/l Parámetro: Ciclohexanol - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos), S (Significa que el indicador biológico es un indicador de exposición al agente químico en cuestión, pero la interpretación cuantitativa de su medida es ambigua (semicuantitativa). Estos indicadores biológicos deben utilizarse como una prueba de selección (screening) cuando no se pueda realizar una prueba cuantitativa o usarse como prueba de confirmación, si la prueba cuantitativa no es específica y el origen del determinante es dudoso), Con hidrólisis
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>cyclohexanol (108-93-0)</b>	
<b>France - Occupational Exposure Limits</b>	
Local name	Cyclohexanol
VME (OEL TWA)	200 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	50 ppm

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>cyclohexanol (108-93-0)</b>	
VLE (OEL C/STEL)	300 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	75 ppm
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Spain - Occupational Exposure Limits</b>	
Local name	Ciclohexanol
VLA-ED (OEL TWA) [1]	208 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	50 ppm
Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>2-ethylhexanoic acid (149-57-5)</b>	
<b>Spain - Occupational Exposure Limits</b>	
Local name	Ácido 2-etilhexanoico
VLA-ED (OEL TWA) [1]	5 mg/m <sup>3</sup>
Notes	FIV (Fracción inhalable y vapor. La notación FIV señala a aquellos agentes químicos que se pueden presentar en el ambiente de trabajo, tanto en forma de materia particulada como vapor, por lo que las dos fases pueden coexistir, contribuyendo ambas a la exposición. Esta situación se puede dar, principalmente, en los siguientes casos: • Cuando el agente en cuestión tiene un valor "intermedio" de presión de vapor (en estos casos se tiene en cuenta la relación entre su concentración en el aire saturado de vapor y el valor del VLA-ED® y la nota se asigna, generalmente, cuando el cociente entre ambas cantidades se encuentra entre 0.1 y 10). • Por razón de la forma de uso del agente químico (por ejemplo, pulverización). • En los procesos que conlleven cambios importantes de temperatura que puedan afectar al estado físico del agente químico. • En los procesos en los que una fracción significativa del vapor puede disolverse o adsorberse en las partículas de otra sustancia, a semejanza de lo que ocurre con los agentes solubles en agua en ambientes con humedad elevada).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>Lavandin Oil (8022-15-9)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.249 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.877 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.0889 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.132 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.0889 mg/kg bodyweight/day

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one (76-22-2)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	10 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	17.6316 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	4.3478 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	5 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	9.303 µg/l
PNEC aqua (marine water)	0.9303 µg/l
PNEC aqua (intermittent, freshwater)	93.03 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.139 mg/kg dwt
PNEC sediment (marine water)	0.0139 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2.17 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	5.56 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	1 mg/l
<b>Naphthenic acid (1338-24-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, dermal	1.81 mg/cm <sup>2</sup>
Long-term - systemic effects, dermal	3.33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	7.76 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - local effects, dermal	0.9 mg/cm <sup>2</sup>
Long-term - systemic effects, oral	0.167 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.91 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	1.67 mg/kg bodyweight/day
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	0.13 mg/l
<b>acetic acid 100% (64-19-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	25 mg/m <sup>3</sup>
Long-term - local effects, inhalation	25 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - local effects, inhalation	25 mg/m <sup>3</sup>

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>acetic acid 100% (64-19-7)</b>	
Long-term - local effects, inhalation	25 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	3.058 mg/l
PNEC aqua (marine water)	0.3058 mg/l
PNEC aqua (intermittent, freshwater)	30.58 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	11.36 mg/kg dwt
PNEC sediment (marine water)	1.136 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.47 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	85 mg/l
<b>Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines (68410-23-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	1.1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3.9 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.56 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.97 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.56 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.00411 mg/l
PNEC aqua (marine water)	0.000411 mg/l
PNEC aqua (intermittent, freshwater)	0.0411 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	411.01 mg/kg dwt
PNEC sediment (marine water)	41.1 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	82.18 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	3.14 mg/l
<b>cyclohexanone (108-94-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	4 mg/kg bodyweight/day
Acute - systemic effects, inhalation	80 mg/m <sup>3</sup>
Acute - local effects, inhalation	80 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	40 mg/m <sup>3</sup>

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>cyclohexanone (108-94-1)</b>	
Long-term - local effects, inhalation	40 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	1 mg/kg bodyweight
Acute - systemic effects, inhalation	20 mg/kg bodyweight/day
Acute - systemic effects, oral	1.5 mg/kg bodyweight
Acute - local effects, inhalation	40 mg/m <sup>3</sup>
Long-term - systemic effects, oral	1.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	10 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - local effects, inhalation	20 mg/m <sup>3</sup>
<b>cyclohexanol (108-93-0)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	3.58 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	130 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	1.79 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	32.5 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	1.79 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.017 mg/l
PNEC aqua (marine water)	0.0017 mg/l
PNEC aqua (intermittent, freshwater)	0.17 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.042 mg/kg dwt
PNEC sediment (marine water)	0.0042 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.005 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	199.5 mg/l
<b>2-ethylhexanoic acid (149-57-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3.5 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-ethylhexanoic acid (149-57-5)	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.36 mg/l
PNEC aqua (marine water)	0.036 mg/l
PNEC aqua (intermittent, freshwater)	0.493 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	6.37 mg/kg dwt
PNEC sediment (marine water)	0.637 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1.06 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	71.7 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Gas mask.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses. EN 166

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Consumer exposure controls:

Do not eat, drink or smoke during use. Always wash hands after handling the product. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing.

### Other information:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous liquid.
Colour	: According to product specification.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: ≤ 1100 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: practically insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### 1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one (76-22-2)

LD50 oral	1500 mg/kg bodyweight
-----------	-----------------------

#### Oils, peppermint (8006-90-4)

LD50 oral rat	2426 mg/kg
---------------	------------

#### acetic acid 100% (64-19-7)

LD50 oral rat	3310 mg/kg Delaware State Medical Journal. Vol. 31, Pg. 276, 1959.
LD50 oral	4960 mg/kg bodyweight Animal: mouse
LD50 dermal	1100 mg/kg bodyweight

#### Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines (68410-23-1)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

#### cyclohexanone (108-94-1)

LD50 oral	1890 mg/kg bodyweight
LD50 dermal	1100 mg/kg bodyweight
LC50 Inhalation - Rat	> 6.2 mg/l air Animal: rat
LC50 Inhalation - Rat (Vapours)	11 mg/l/4h

#### cyclohexanol (108-93-0)

LD50 oral rat	1400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1260 - 1550
LD50 oral	1400 mg/kg bodyweight
LC50 Inhalation - Rat	> 3.6 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapours)	11 mg/l/4h

#### 2-ethylhexanoic acid (149-57-5)

LD50 oral rat	2043 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1445 - 2890
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

#### Fennel oil, sweet (84455-29-8)

LD50 oral	3004 mg/kg bodyweight
-----------	-----------------------

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye damage.



# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

### 1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one (76-22-2)

STOT-single exposure	May cause damage to organs.
----------------------	-----------------------------

### cyclohexanol (108-93-0)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

### acetic acid 100% (64-19-7)

NOAEL (oral, rat, 90 days)	290 mg/kg bodyweight Animal: rat, Animal sex: male
----------------------------	--

### Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines (68410-23-1)

NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	--

### cyclohexanone (108-94-1)

NOAEL (oral, rat, 90 days)	143 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	---

### cyclohexanol (108-93-0)

NOAEL (oral, rat, 90 days)	143 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	---

### 2-ethylhexanoic acid (149-57-5)

NOAEL (oral, rat, 90 days)	≈ 300 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
----------------------------	---

Aspiration hazard	: Not classified
-------------------	------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Not rapidly degradable	

### Naphthenic acid (1338-24-5)

LC50 - Fish [1]	≈ 5.62 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	≈ 20 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 29.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	≈ 17.7 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	≈ 29.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	≈ 18.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>acetic acid 100% (64-19-7)</b>	
LC50 - Fish [1]	79 – 273 mg/l Mattson, V.R., J.W. Arthur, and C.T. Walbridge 1976. Acute Toxicity of Selected Organic Compounds to Fathead Minnows. EPA-600/3-76-097, U.S.EPA, Duluth, MN :12 p.
LC50 - Fish [2]	> 300.82 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	52.6 – 180 mg/l Espiritu, E.Q., C.R. Janssen, and G. Persoone 1995. Cyst-Based Toxicity Tests. VII. Evaluation of the 1-h Enzymatic Inhibition Test (Fluotox) with Artemia nauplii. Environ.Toxicol.Water Qual. 10:25-34
EC50 - Crustacea [2]	65 mg/l Janssen, C.R., E.Q. Espiritu, and G. Persoone 1993. Evaluation of the new ""Enzymatic Inhibition"" Criterion for Rapid Toxicity Testing with Daphnia magna. In: A.Soaes and P.Calow (Eds.), Progress in Standardization of Aquatic Toxicity Tests, Lewis Publ. :71-81
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	> 300.82 mg/l Test organisms (species): Skeletonema costatum
<b>Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines (68410-23-1)</b>	
LC50 - Fish [1]	7.07 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	5.18 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.11 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
<b>cyclohexanone (108-94-1)</b>	
LC50 - Fish [1]	527 – 732 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
<b>cyclohexanol (108-93-0)</b>	
LC50 - Fish [1]	704 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	17 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 500 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
<b>2-ethylhexanoic acid (149-57-5)</b>	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	910 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	49.3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

No additional information available

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.3. Bioaccumulative potential

#### acetic acid 100% (64-19-7)

Partition coefficient n-octanol/water (Log Kow)

-0.17 LOG KOW Databank, compiled by Dr. James Sangster, Sangster Research Laboratories, Montreal, Canada, distributed by Technical Database Services (TDS), New York

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Completely empty the packaging prior to decontamination. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Comply with applicable regulations for solid waste disposal.
Additional information	: Flammable vapours may accumulate in the container. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Ecology - waste materials	: Avoid release to the environment. Do not allow into drains or water courses.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>				
PAINT / PAINT RELATED MATERIAL (Oils, spike)	PAINT (Oils, spike)	Paint (Oils, spike)	PAINT (Oils, spike)	PAINT (Oils, spike)
<b>Transport document description</b>				
UN 1263 PAINT / PAINT RELATED MATERIAL (Oils, spike), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT (Oils, spike), 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint (Oils, spike), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT (Oils, spike), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT (Oils, spike), 3, III, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				

# Organometallic dye for industrial use

## Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR) : D/E

#### Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

#### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma

#### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Storage class (LGK, TRGS 510) : LGK 3 - Flammable liquids

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 2A, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.1B, LGK 6.2, LGK 7

Joint storage with restrictions permitted for

: LGK 5.1B, LGK 6.1D, LGK 11, LGK 10-13

Joint storage permitted for

: LGK 2B, LGK 3, LGK 6.1A, LGK 6.1C, LGK 8A, LGK 8B, LGK 10, LGK 12, LGK 13

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms

COD	Chemical oxygen demand (COD)
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS	Chemical Abstracts Service (division of the American Chemical Society)
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
CAS-No.	Chemical Abstract Service number
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms	
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
Pow (log)	n-octanol/water partition coefficient
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Data sources : Classification according to Regulation (EC) No. 1272/2008 [CLP]. ECHA (European Chemicals Agency). Supplier's safety documents.

Full text of H- and EUH-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 2	Flammable solids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

# Organometallic dye for industrial use

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements	
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable