

Safety Data Sheet

according to Regulation (EU) 2015/830
Reference number: 15092021-7
Issue date: 9/15/2021 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : GGP 2067-COPPER
Product code : PMA-GGP-2067-7.4

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Colouring agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier

Heraeus Tokmak A.S.
Kemalpaşa O.S.B. Mah. 37. Sok. No: 6 35170 Ulucak Kemalpaşa
İzmir
TURKEY
T +90 (232) 877 2410
hakan.kiran@heraeus.com - www.heraeustokmak.com

1.4. Emergency telephone number

Emergency number : +90 (232) 877 2410

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1B	H350
Reproductive toxicity, Category 2	H361
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause cancer. Suspected of damaging fertility or the unborn child. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS05

GHS07

GHS08

Signal word (CLP) : Danger

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Contains	: D-Limonenen, Eucalyptus globulus oil, Camphor, Oils, lavandin, Bismuth tris(2-ethylhexanoate), Peppermint oil, Rosin, Butan-1-ol, Formaldehyde, turpentine, oil, Naphthenic acid, Naphthenic acids, vanadyl complexes
Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H350 - May cause cancer. H361 - Suspected of damaging fertility or the unborn child. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours, spray, mist. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P501 - Dispose of contents and container to an approved waste disposal plant.
Extra phrases	: Restricted to professional users. For professional users only.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Terpineol	CAS-No.: 8000-41-7 EC-No.: 232-268-1	≥ 10 – < 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Urea, polymer with formaldehyde, butylated	CAS-No.: 68002-19-7 EC-No.: 614-202-7	≥ 10 – < 25	Aquatic Chronic 4, H413
Butan-1-ol	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6	≥ 5 – < 10	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
Rosin	CAS-No.: 8050-09-7 EC-No.: 232-475-7 EC Index-No.: 650-015-00-7	≥ 5 – < 10	Skin Sens. 1, H317
Spikoel	CAS-No.: 8016-78-2 EC-No.: 284-290-6	≥ 3 – < 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315
Polybutyl titanate	CAS-No.: 9022-96-2 EC-No.: 638-841-6	≥ 3 – < 5	Flam. Liq. 3, H226 Eye Irrit. 2, H319

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bismuth tris(2-ethylhexanoate)	CAS-No.: 67874-71-9 EC-No.: 267-499-7	≥ 3 – < 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d
turpentine, oil	CAS-No.: 8006-64-2 EC-No.: 232-350-7 EC Index-No.: 650-002-00-6	≥ 3 – < 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Naphthenic acid	CAS-No.: 1338-24-5 EC-No.: 215-662-8	≥ 1 – < 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Camphor	CAS-No.: 76-22-2 EC-No.: 200-945-0	≥ 1 – < 3	Flam. Sol. 1, H228 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 2, H371
Peppermint oil	CAS-No.: 8006-90-4	≥ 1 – < 3	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Oils, lavandin	CAS-No.: 8022-15-9	≥ 1 – < 3	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
o-Xylene substance with a Community workplace exposure limit	CAS-No.: 95-47-6 EC-No.: 202-422-2 EC Index-No.: 601-022-00-9	≥ 1 – < 3	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
sulfur	CAS-No.: 7704-34-9 EC-No.: 231-722-6 EC Index-No.: 016-094-00-1	≥ 1 – < 3	Skin Irrit. 2, H315
D-Limonenen	CAS-No.: 8008-56-8 EC-No.: 284-515-8	≥ 1 – < 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Eucalyptus globulus oil	CAS-No.: 8000-48-4 EC-No.: 616-775-9	≥ 1 – < 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Naphthenic acids, vanadyl complexes	CAS-No.: 68553-60-6 EC-No.: 271-395-7	≥ 1 – < 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
toluene substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≥ 0.1 – < 1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336
2-ethylhexanoic acid	CAS-No.: 149-57-5 EC-No.: 205-743-6 EC Index-No.: 607-230-00-6	≥ 0.1 – < 1	Repr. 2, H361d
Formaldehyde substance with a Community workplace exposure limit	CAS-No.: 50-00-0 EC-No.: 200-001-8 EC Index-No.: 605-001-00-5	0.1 – 0.2	Carc. 1B, H350 Muta. 2, H341 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Skin Sens. 1, H317

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Formaldehyde	CAS-No.: 50-00-0 EC-No.: 200-001-8 EC Index-No.: 605-001-00-5	(0.2 ≤ C ≤ 100) Skin Sens. 1, H317 (5 ≤ C < 25) Eye Irrit. 2, H319 (5 ≤ C < 25) Skin Irrit. 2, H315 (5 ≤ C ≤ 100) STOT SE 3, H335 (25 ≤ C ≤ 100) Skin Corr. 1B, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

5.2. Special hazards arising from the substance or mixture

- | | |
|--|--|
| Fire hazard | : Flammable liquid and vapour. |
| Explosion hazard | : Risk of explosion if heated under confinement. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Advice for firefighters

- | | |
|--------------------------------|--|
| Precautionary measures fire | : Exercise caution when fighting any chemical fire. Keep upwind. Eliminate all ignition sources if safe to do so. |
| Firefighting instructions | : Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- | | |
|----------------------|--|
| Emergency procedures | : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapours/spray. |
|----------------------|--|

6.1.2. For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. |

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. |
| Methods for cleaning up | : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. |
| Hygiene measures | : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-(2-butoxyethoxy)ethyl acetate (124-17-4)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-(2-Butoxyethoxy)ethylacetat
AGW (OEL TWA) [1]	67 mg/m ³
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	1,5(l)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900
Kerosine (petroleum) (8008-20-6)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Kerosin (Erdöl) (C9 – C14 Aliphaten)
AGW (OEL TWA) [1]	Siehe TRGS 900, Nummer 2.9
Remark	AGS - Ausschuss für Gefahrstoffe; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Butan-1-ol (71-36-3)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Butan-1-ol
AGW (OEL TWA) [1]	310 mg/m ³
AGW (OEL TWA) [2]	100 ppm
Peak exposure limitation factor	1(l)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Butan-1-ol (1-Butanol)

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Butan-1-ol (71-36-3)	
Biological limit value	2 mg/g creatinine Parameter: Butan-1-ol (1-Butanol) (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: d) vor nachfolgender Schicht - Festlegung/Begründung: 05/2013 DFG 10 mg/g creatinine Parameter: Butan-1-ol (1-Butanol) (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 05/2013 DFG
Regulatory reference	TRGS 903
o-Xylene (95-47-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	o-Xylene
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Xylol (alle Isomeren)
AGW (OEL TWA) [1]	220 mg/m ³
AGW (OEL TWA) [2]	50 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv
Regulatory reference	TRGS900
Formaldehyde (50-00-0)	
EU - Binding Occupational Exposure Limit (BOEL)	
Local name	Formaldehyde
BOEL TWA	0.37 mg/m ³ 0.62 mg/m ³ (Limit value for the health care, funeral and embalming sectors until 11 July 2024)
BOEL TWA [ppm]	0.3 ppm 0.5 ppm (Limit value for the health care, funeral and embalming sectors until 11 July 2024)
BOEL STEL	0.74 mg/m ³
BOEL STEL [ppm]	0.6 ppm
Notes	Dermal sensitisation
Regulatory reference	DIRECTIVE (EU) 2019/983 (amending Directive 2004/37/EC)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Formaldehyd
AGW (OEL TWA) [1]	0.37 mg/m ³
AGW (OEL TWA) [2]	0.3 ppm
Peak exposure limitation factor	2(I)

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Formaldehyde (50-00-0)	
Remark	AGS - Ausschuss für Gefahrstoffe; Sh - Hautsensibilisierender Stoff; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; X - Krebserzeugender Stoff der Kat. 1A oder 1B oder krebserzeugende Tätigkeit oder Verfahren nach § 2 Absatz 3 Nr. 4 der Gefahrstoffverordnung – es ist zusätzlich § 10 GefStoffV zu beachten
Regulatory reference	TRGS900
toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOEL TWA [ppm]	50 ppm
IOEL STEL	384 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Toluol
AGW (OEL TWA) [1]	190 mg/m ³
AGW (OEL TWA) [2]	50 ppm
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Toluol
Biological limit value	600 µg/l Parameter: Toluol - Untersuchungsmaterial: B = Vollblut - Probenahmezeitpunkt: g) unmittelbar nach Exposition - Festlegung/Begründung: 11/2017 DFG 75 µg/l Parameter: Toluol - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2018 DFG 1.5 mg/l Parameter: o-Kresol (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2018 DFG
Regulatory reference	TRGS 903

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective goggles. Full protective flameproof clothing. Gas mask.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. EN 374

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: gel.
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 35 °C (1013 hPa)
Flash point	: 40 °C (1013 hPa)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: ≤ 1100 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Practically insoluble in : Water. (20 °C). (1013 hPa).
Partition coefficient n-octanol/water (Log Pow)	: No data available

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Viscosity, kinematic	: No data available
Viscosity, dynamic	: 3000 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-(2-butoxyethoxy)ethyl acetate (124-17-4)

LD50 oral rat	11920 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 10880 - 13100
LD50 oral	2340 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1900 - 2880

Bismuth tris(2-ethylhexanoate) (67874-71-9)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	--

Rosin (8050-09-7)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
-----------------	--

o-Xylene (95-47-6)

LD50 oral rat	> 3567 mg/kg (RTECS)
LD50 dermal rabbit	14100 mg/kg (Japan GHS Basis for Classification Data)

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

o-Xylene (95-47-6)	
LC50 Inhalation - Rat	4300 ppm
Spikoel (8016-78-2)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Formaldehyde (50-00-0)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
Camphor (76-22-2)	
STOT-single exposure	May cause damage to organs.
Rhodium tris(2-ethylhexanoate) (20845-92-5)	
STOT-single exposure	May cause drowsiness or dizziness.
Butan-1-ol (71-36-3)	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
o-Xylene (95-47-6)	
STOT-single exposure	May cause respiratory irritation.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
2-(2-butoxyethoxy)ethyl acetate (124-17-4)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Bismuth tris(2-ethylhexanoate) (67874-71-9)	
NOAEL (subchronic, oral, animal/male, 90 days)	180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:
NOAEL (subchronic, oral, animal/female, 90 days)	205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:
toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Naphthenic acid (1338-24-5)	
NOAEL (oral, rat, 90 days)	302 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Not rapidly degradable

2-(2-butoxyethoxy)ethyl acetate (124-17-4)

LC50 - Fish [1]	50 – 70 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	1570 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	520 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Bismuth tris(2-ethylhexanoate) (67874-71-9)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Rosin (8050-09-7)

LC50 - Fish [1]	5.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	5.4 mg/l Test organisms (species):

o-Xylene (95-47-6)

EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.714 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

Naphthenic acid (1338-24-5)

LC50 - Fish [1]	≈ 5.62 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	≈ 20 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 29.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	≈ 17.7 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	≈ 29.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	≈ 18.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

o-Xylene (95-47-6)

Partition coefficient n-octanol/water (Log Pow)	3.12 (20 °C)
---	--------------

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

o-Xylene (95-47-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--------------------	---

12.6. Other adverse effects

No additional information available






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT / PAINT RELATED MATERIAL	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT / PAINT RELATED MATERIAL, 3, III, (D/E)	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III	UN 1263 PAINT, 3, III	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				


GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
28.	Formaldehyde	Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.
48.	toluene	Toluene
72.	Formaldehyde	The substances listed in column 1 of the Table in Appendix 12

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG) Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
Storage class (LGK, TRGS 510)	: LGK 3 - Flammable liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Abbreviations and acronyms:	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources

: ECHA (European Chemicals Agency). REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. Supplier's safety documents.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

GGP 2067-COPPER

Safety Data Sheet

according to Regulation (EU) 2015/830

Full text of H- and EUH-statements:

H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.